



Product Information ST-A.21.03

AVIA ATF 8HP

Description	<p>A very high graded automatic transmission fluid based on special selected synthetic base oils, with a high viscosity index and a number of selected additives to obtain the following properties:</p> <ul style="list-style-type: none">- important contribution fuel economy- excellent lubrication- very good resistance against oxidation and a very high thermal stability- excellent and very stable friction characteristics that enable longer oil-replacement intervals- excellent resistance against foaming- excellent protection against wear- a very high and stable viscosity index- green coloured												
Application	<p>This premium synthetic product is specially formulated for the lubrication of ZF 8HP transmissions. This oil contributes greatly to realizing fuel saving and can be used amongst others in the ZF 8HP transmissions 8HP45, 8HP55, 8HP70 and 8HP90. It can also be used in certain ZF 6HP transmissions, which are used in various VAG models.</p>												
Specifications	<p>Performance level BMW 8322 2152426/2289720(ATF3+) ; Chrysler 68157995AA Fiat 9.55550-AV5 ; Jaguar 02JDE 26444 ; Land Rover LR023288 VAG G-060-162</p>												
Typicals	<table><tr><td>Density at 15 °C, kg/l</td><td>0,842</td></tr><tr><td>Viscosity 40 °C, mm²/s</td><td>25,80</td></tr><tr><td>Viscosity 100 °C, mm²/s</td><td>6,00</td></tr><tr><td>Viscosity Index</td><td>190</td></tr><tr><td>Flash Point COC, °C</td><td>198</td></tr><tr><td>Pour Point, °C</td><td>-51</td></tr></table>	Density at 15 °C, kg/l	0,842	Viscosity 40 °C, mm ² /s	25,80	Viscosity 100 °C, mm ² /s	6,00	Viscosity Index	190	Flash Point COC, °C	198	Pour Point, °C	-51
Density at 15 °C, kg/l	0,842												
Viscosity 40 °C, mm ² /s	25,80												
Viscosity 100 °C, mm ² /s	6,00												
Viscosity Index	190												
Flash Point COC, °C	198												
Pour Point, °C	-51												
	<p>The above figures are typical of those obtained with normal production batch, they are not a technical specification, due to continuous development of the product, they may change.</p>												
Packaging	1L,4L,20L,206L												
Storage	<p>All packages should be stored under a roof. If they are stored in the open air where they can be exposed to atmospheric conditions - rain, they should be placed in a horizontal position, so as to prevent ingress of water and prevent the destruction of marking, it is best to use canvas.</p>												
Health, Occupational Health and Safety, Environment	<p>Safety information is included in the Safety Data Sheet (SDS Safety Data Sheet). It contains detailed information on the potential hazards, precautions and First Aid measures, together with information on the impact on the environment and the disposal of used products. UNIMOT S.A. AVIA POLSKA and cooperating companies do not take responsibility for the consequences of improper product use or non-use of the precautions. Before using the product for purposes other than those listed, please consult your local UNIMOT S.A. AVIA POLSKA office.</p>												