



## Product Information ST-A.25.01

### AVIA Brake Fluid DOT 4

<b>Description</b>	A synthetic brake fluid having the following properties: <ul style="list-style-type: none"><li>- good resistance against ageing</li><li>- a very good compatibility with seals and gaskets</li><li>- minimal corrosion tendency</li><li>- high wet boiling point</li><li>- optimal viscosity at low temperatures</li></ul>	
<b>Application</b>	Applicable for all hydraulic brake systems with drum or disk brakes requiring a synthetic brake fluid and where a brake fluid of the type DOT 4 is prescribed.	
<b>Performance Level</b>	Performance level FMVSS 116 DOT 4 SAE J1703, ISO 4925	
<b>Typicals</b>	Density at 15 °C, kg/l	1,030
	Viscosity 40 °C, mm <sup>2</sup> /s	1200
	Viscosity 100 °C, mm <sup>2</sup> /s	2,30
	Boiling Point (reflux) , °C	263
	Wet Boiling Point, °C	168
	pH - 50% in	8,0

The above figures are typical of those obtained with normal production batch, they are not a technical specification, due to continuous development of the product, they may change.

**Packaging** 1L,4L,20L,206L

**Storage** All packages should be stored under a roof. If they are stored in the open air where they can be exposed to atmospheric conditions - rain, they should be placed in a horizontal position, so as to prevent ingress of water and prevent the destruction of marking, it is best to use canvas.

### Health, Occupational Health and Safety, Environment

Safety information is included in the Safety Data Sheet (SDS Safety Data Sheet). It contains detailed information on the potential hazards, precautions and First Aid measures, together with information on the impact on the environment and the disposal of used products. UNIMOT S.A. AVIA POLSKA and cooperating companies do not take responsibility for the consequences of improper product use or non-use of the precautions. Before using the product for purposes other than those listed, please consult your local UNIMOT S.A. AVIA POLSKA office.