



Product Information ZX-A.80.09

## AVIA ECOSYNTH Super Plus C2/C3 5W30

### Description

A synthetic universal motor oil, developed according the most recent technology, based on specially selected synthetic base oils to which special additives are added to obtain the following properties:

- a fast cold start
- a safe lubrication film at high temperatures
- a very good detergency and dispersion
- a very strong protection against wear, corrosion and foaming

### Application

This synthetic universal "mid SAPS" motor oil is recommended for use in petrol and diesel engines, with or without turbo-charging, in passenger cars and delivery vans. Due to its low SAPS content this product can be applied in vehicles with modern three way catalysts and diesel particle filters.

### Specifications

Performance level  
ACEA C2, C3  
API SN  
BMW Longlife-04  
GM dexos 2  
MB 229.51/229.52  
Porsche C30  
VW 505.01

### Typicals

Density at 15 °C, kg/l	0,848
Viscosity -30 °C, mPa.s	6400
Viscosity 40 °C, mm <sup>2</sup> /s	74,40
Viscosity 100 °C, mm <sup>2</sup> /s	12,30
Viscosity Index	163
Flash Point COC, °C	242
Pour Point, °C	-36
Total Base Number, mgKOH/g	7,8
Sulphate Ash, %	0,77